

# **ASX RELEASE**

## 28 October 2016

#### About Globe

- Globe Metals & Mining Limited is a Perth based company listed on Australian Stock Exchange (ASX Code: GBE)
- Globe's principal focus is the Kanyika Niobium Project.
- The Kanyika Niobium Project host to a 2004 JORC compliant Mineral Resource Estimate of 68.3M tonnes of  $Nb_2O_5$  using a 1,500 ppm  $Nb_2O_5$  cut-off (refer ASX announcement dated 7 January 2013).

#### **Investment Summary**

• 100% interest held on projects in Malawi (Africa) including niobium and graphite

#### **Directors and Management**

Ms Alice Wong - Non-Executive Chairperson Mr Alistair Stephens - Managing Director Mr William Hayden - Non-executive Director Mr Bo Tan - Non-executive Director Mr Alex Ko - Non-executive Director

#### **Capital Structure**

Shares on Issue: 469,729,062 Options on Issue: 4,000,000 (various) Last Price (27/10/2016): \$0.021 Market Capitalisation: circa \$10 million

#### **Substantial Shareholders**

Apollo Metals: 52.37% Ao-Zhong International Minerals: 25.15%

#### Contact

Alistair Stephens Managing Director <u>info@globemm.com</u> T: +61 (0)8 9327 0700

## September Quarter 2016 Review of Operations

## Summary

### **Strategic Review**

- Globe is actively reviewing cash flow generating opportunities unconstrained by business sector or nature.
- Globe has identified the Australia-China trade in agricultural products, and food and beverage as a key area of interest and focus.
- Globe has and continues to review a number of investment opportunities in this area.
- Globe remains optimistic of being able to deliver a strategic initiative within a modest timeframe.

## Kanyika Niobium Project

- Company continues to negotiate with various regulators, stakeholders and parties to maintain opportunistic development options.
- Work during the quarter included consideration of project financing options.

### **Corporate & Finance**

- Cash at bank and in term deposits at 30 September 2016 of \$12.73 million.
- Notice for upcoming 2016 Annual General Meeting has been despatched to shareholders and was lodged with ASX on 19 October 2016.
- The 2016 Annual General Meeting will take place at 11am (WST) on Tuesday, 29 November 2016 at Level 1, 35-37 Havelock Street, West Perth, Western Australia.



Globe Metals & Mining Limited (ASX Code: GBE) ("Globe" or "the Company") provides its activities report for the quarter ended 30 September 2016.

## 1. Strategic Review

As announced on 11 December 2015, Globe is undertaking a strategic review of business and global investment opportunities outside of the mining and metals industry.

The strategic review has identified the burgeoning trade in agricultural products, and food and beverage between Australia and China as a key area of interest and focus, due to its growth opportunities and for the fact that it is considered a good fit with the Company's networks and capabilities.

Globe has and continues to review a number of investment opportunities in this area. Shareholders will be updated on developments as they occur.

## 2. Kanyika Niobium Project

## 2.1 Overview

A Mineral Resource Statement was published on 7 January 2013 (refer ASX release) stating a mineral resource inventory of 68.3M tonnes (equivalent) of  $Nb_2O_5$  using a 1,500 ppm  $Nb_2O_5$  cut-off (refer Tables 1 & 2 below). No additions or changes have been made to this resource statement and it complies with the 2004 JORC guidelines for mineral resource statements as made in that release, (refer to the "Competent Persons Statement" section on page 8).

Table 1: Mineral	<b>Resource Estima</b>	te for Kany	vika using a	1.500 pp	m Nb <sub>2</sub> O <sub>F</sub>	lower cut
Tuble 1. Willicial	Resource Estime			-,500 pp		lower cat

Category	Million Tonnes	Nb₂O₅ ppm	Ta₂O₅ ppm
Measured	5.3	3,790	180
Indicated	47.0	2,860	135
Inferred	16.0	2,430	120
Total	68.3	2,830	135

### Table 2: Mineral Resource Estimate for Kanyika using a 3,000 ppm $Nb_2O_5$ lower cut

Category	Million Tonnes	Nb₂O₅ ppm	Ta₂O₅ ppm
Measured	3.4	4,790	220
Indicated	16.6	4,120	190
Inferred	2.8	4,110	190
Total	22.8	4,220	190



## 2.2 Mining Development Process

Negotiations with various regulators, stakeholders and other parties are ongoing in regard to developing the Kanyika project. Various options for project development are being considered. Financing options are progressing and co-development opportunities are being actively explored.

## 2.3 Exploration Activities

No exploration activities have been undertaken this quarter.

### 3. Corporate

### 3.1 Cash at Bank

Cash at bank for the Company remains robust with A\$12.73M at bank on call or in term deposit.

### 3.2 Options

As at 30 September 2016, share options remaining on issue are as follows:

Grant Date	Expiry Date	Number	Exercise Price
2 July 2013	30 June 2017	1,000,000	\$0.10
2 July 2013	30 June 2018	1,000,000	\$0.15
2 July 2013	30 June 2019	1,000,000	\$0.20
2 July 2013	30 June 2020	1,000,000	\$0.25
		4,000,000	

### 4. Schedule of Mineral Tenements as at 30 June 2016

	Project	Status	Tenement	Interest held by Globe
Malaud	Kanyika	Granted	EPL0421/15 ML*	100%
Malawi	Chiziro	Granted	EPL0299/10R	100%

ML\*- ID number pending completion of DA negotiations EPL – Exclusive Prospecting Licence (Malawi)

L – Exclusive Prospecting Licence (Mozambique)

END

Contact: Alistair Stephens Managing Director Globe Metals & Mining Ltd Tel: +61 (0) 8 9327 0700



**Competent person:** The contents of this report relating to the Mineral Resource Estimate are based on information compiled by Mr Michael Job, Fellow of the Australasian Institute of Mining and Metallurgy, and a consultant employed by Quantitative Group at the time the Mineral Resource Estimate was completed. Mr Job had sufficient experience related to the activity undertaken to qualify as a "Competent person", as defined in the 2004 edition of the Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves and consented to the inclusion in reports of matters compiled by him in the form and context which they appear. The Mineral Resource Estimate was first reported to the ASX on 7 January 2013 and has not been updated since.

**Competent person:** The information in this report that relates to Exploration Targets, Exploration Results, Mineral Resources or Ore Reserves is based on information compiled by Mr Fergus Jockel, a Member of The Australasian Institute of Mining and Metallurgy and the Australian Institute of Geoscientists, who was a full-time employee of the Company at the time the information was prepared. Mr Jockel had sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activity being undertaken to qualify as a Competent Person as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'. Mr Jockel consented to the inclusion in reports of information compiled by him in the form and context in which they appear.



## JORC TABLE 1

## Section 1 Sampling Techniques and Data

Criteria	Explanation	Commentary
Sampling	• Nature and quality of sampling (eg cut	Rock chip samples were collected by
techniques	channels, random chips, or specific	Globe Metals and Mining Ltd where
	specialised industry standard	suitable outcrop was identified.
	measurement tools appropriate to the	Samples were collected for TGC
	minerals under investigation, such as	analysis at the Bureau Veritas
	down hole gamma sondes, or	Inspectorate Laboratories Pty Ltd (BV)
	handheld XRF instruments, etc). These	in Rustenburg South Africa. Sampling
	examples should not be taken as	points were selected to ensure
	limiting the broad meaning of	representation of fresh rock and
	sampling.	saprock.
	Include reference to measures taken to	<ul> <li>Approximately 2kg samples were</li> </ul>
	ensure sample representivity and the	collected. Bagging and numbering
	appropriate calibration of any	were done in the field to ensure
	measurement tools or systems used.	representivity of the sampling
	Aspects of the determination of	process.
	mineralisation that are Material to the	<ul> <li>Sample preparation was carried out by</li> </ul>
	standard' work has been done this	BV. The samples were acidified and
	would be relatively simple (eq. 'reverse	roasted to remove carbonate and
	circulation drilling was used to obtain	organic carbon. The residual carbon
	1 m samples from which 3 ka was	was determined by using a total
	nulverised to produce a 30 a charae for	compustion analyser.
	fire assav) In other cases more	
	explanation may be required, such as	
	where there is coarse aold that has	
	inherent sampling problems. Unusual	
	commodities or mineralisation types	
	(eg submarine nodules) may warrant	
	disclosure of detailed information.	
Drilling	• Drill type (eg core, reverse circulation,	• N/A
techniques	open-hole hammer, rotary air blast,	
	auger, Bangka, sonic, etc) and details	
	(eg core diameter, triple or standard	
	tube, depth of diamond tails, face-	
	sampling bit or other type, whether	
	core is oriented and if so, by what	
	method, etc).	
Drill sample	Method of recording and assessing	• N/A
recovery	core and chip sample recoveries and	
	results assessed.	
	ivieusures tuken to maximise sample     recovery and ensure representative	
	nature of the samples	
	<ul> <li>Whether a relationship exists between</li> </ul>	
	sample recovery and grade and	
	whether sample hias may have	
	occurred due to preferential loss/agin	
	of fine/coarse material.	



Criteria	Explanation	Commentary
Logging	<ul> <li>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</li> <li>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</li> <li>The total length and percentage of the relevant intersections logged.</li> </ul>	<ul> <li>All rock chip samples were geologically logged following Globe Metals and Mining procedure.</li> </ul>
Sub-sampling techniques and sample preparation	<ul> <li>If core, whether cut or sawn and whether quarter, half or all core taken.</li> <li>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</li> <li>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</li> <li>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</li> <li>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</li> <li>Whether sample sizes are appropriate to the grain size of the material being sampled.</li> </ul>	<ul> <li>At BV the samples were sorted, dried and weighed. Primary preparation involved crushing the whole sample. Sample splitting was done through a riffle splitter to obtain a sub-fraction later pulverised in a vibrating pulveriser.</li> </ul>
Quality of assay data and laboratory tests	<ul> <li>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</li> <li>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</li> <li>Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.</li> </ul>	<ul> <li>All rock chip and samples were assayed TGC analysis at the Bureau Veritas Inspectorate Laboratories Pty Ltd in South Africa.</li> <li>Internal Laboratory Standards and Repeats were performed on the batch of 40 samples.</li> <li>Quality control procedures adopted by BV are considered to be adequate.</li> </ul>



Verification of sampling and assayingThe verification of significant intersections by either independent or alternative company personnel.Globe Metal and Mining geologist verified all samples prior to dispatch to the laboratory.2. Documentation of primary data, data entry procedures, data verification, data storage [physical and electronic) protocols.Documentation of primary data, data entry procedures, data verification, data storage [physical and electronic) protocols.Documentation of primary data, data entry procedures, data verification, data storage [physical and electronic) protocols.Documentation of primary data, dataLocation of data pointsAccuracy and quality of surveys used to locate drill holes (collar and down- hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.Hand held GPS units (GARMIN GPSMAP 783) are used to define field to locate drill holes (collar and down- hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.Hand held GPS units (GARMIN GPSMAP 783) are used to define field to locate drill holes (collar and down- hole surveys), trenches mine workings and data pointsHand held GPS units (GARMIN GPSMAP 785) are used to define field to location of the grid system used.Data spacing and distributionData spacing (or reporting of Exploration Results.Sample locations were selected after nature of graphite mineralisation encountered during mapping to ensure all the nature of graphite mineralisation encountered during mapping were represented.Orientation of geological and distribution to geological and proceed to fease estimation of sampling orientation and the orienta	Criteria	Explanation	Commentary
Location of data points• Accuracy and quality of surveys used to locate drill holes (collar and down- hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.• Hand held GPS units (GARMIN GPSMAP 78s) are used to define field location of rock chop samples. These locations are considered accurate to Sm. The GPS has sufficient topographic control warranted for rock chip sampling. GPS data is downhoaded via MAP SOURCE into MS Excel.Data spacing and distribution• Data spacing for reporting of Exploration Results. • Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.• N/AOrientation of data in relation to geological structure• Whether the orientation of sampling orientation and the orientation of have introduced a sampling of possible structures is nown, considering the deposit type. • If the relationship between the drilling orientation and the orientation of kave introduced a sampling bias, this should be assessed and reported if material.• N/ASample security.• The measures taken to ensure sample security.• Chain of custody for Globe Metal and Mining rock chip was managed in the field by the geology manager. Samples were collected from the Lilongwe office in Malawi by MANICA (freight company in Malawi) for delivery to Bureau Veritas in South Africa.	Verification of sampling and assaying	<ul> <li>The verification of significant intersections by either independent or alternative company personnel.</li> <li>The use of twinned holes.</li> <li>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</li> <li>Discuss any adjustment to assay data.</li> </ul>	<ul> <li>Globe Metal and Mining geologist verified all samples prior to dispatch to the laboratory.</li> <li>Documentation of samples is initially collected in notebooks and location stored in hand held GPS units before being transferred to electronic format.</li> </ul>
Data spacing and distributionData spacing for reporting of Exploration Results.Sample locations were selected after geological mapping to ensure all the nature of graphite mineralisation encountered during mapping were represented.distribution• Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.• N/AOrientation of data in relation to geological structure• Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.• Chain of custody for Globe Metal and Mining rock chip was managed in the field by the geology manager. Samples were collected from the Lilongwe office in Malawi by MANICA (freight company in Malawi for delivery to Bureau Veritas in South Africa.	Location of data points	<ul> <li>Accuracy and quality of surveys used to locate drill holes (collar and down- hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</li> <li>Specification of the grid system used.</li> <li>Quality and adequacy of topographic control.</li> </ul>	<ul> <li>Hand held GPS units (GARMIN GPSMAP 78s) are used to define field location of rock chop samples. These locations are considered accurate to 5m. The GPS has sufficient topographic control warranted for rock chip sampling. GPS data is downloaded via MAP SOURCE into MS Excel.</li> </ul>
Orientation of data in relation to geological• Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. • If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.• N/ASample security• The measures taken to ensure sample security.• Chain of custody for Globe Metal and Mining rock chip was managed in the field by the geology manager. Samples were collected from the Lilongwe office in Malawi by MANICA (freight company in Malawi) for delivery to Bureau Veritas in South Africa.	Data spacing and distribution	<ul> <li>Data spacing for reporting of Exploration Results.</li> <li>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</li> <li>Whether sample compositing has been applied.</li> </ul>	<ul> <li>Sample locations were selected after geological mapping to ensure all the nature of graphite mineralisation encountered during mapping were represented.</li> </ul>
Sample security       • The measures taken to ensure sample security.       • Chain of custody for Globe Metal and Mining rock chip was managed in the field by the geology manager. Samples were collected from the Lilongwe office in Malawi by MANICA (freight company in Malawi) for delivery to Bureau Veritas in South Africa.	Orientation of data in relation to geological structure	<ul> <li>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</li> <li>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</li> </ul>	• N/A
Audits or       • The results of any audits or reviews of       • No audit of data has been completed         reviews       • ampling techniques and data       • adots	Sample security Audits or	<ul> <li>The measures taken to ensure sample security.</li> <li>The results of any audits or reviews of sampling techniques and data</li> </ul>	<ul> <li>Chain of custody for Globe Metal and Mining rock chip was managed in the field by the geology manager. Samples were collected from the Lilongwe office in Malawi by MANICA (freight company in Malawi) for delivery to Bureau Veritas in South Africa.</li> <li>No audit of data has been completed to data</li> </ul>



Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	Explanation	Commentary
Mineral tenement and land tenure status	<ul> <li>Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</li> <li>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</li> </ul>	<ul> <li><u>Chiziro Graphite Project</u></li> <li>Exploration is conducted within EPL0299/10<b>R2</b> which is 100% held by Globe Metals and Mining Ltd. The EPL covers an area of <b>835.1</b>km<sup>2</sup>.</li> <li>The tenement is in good standing and no known impediments exist.</li> </ul>
Exploration done by other parties	<ul> <li>Acknowledgment and appraisal of exploration by other parties.</li> </ul>	<ul> <li>The previous licence holder - Fergie Minerals and Metals Ltd - did not carry out any geological work. All exploration work to date has been conducted by Globe Metals and Mining Ltd only.</li> </ul>
Geology	<ul> <li>Deposit type, geological setting and style of mineralisation.</li> </ul>	<ul> <li>The licence area is underlain by gneisses, schists and granulites which belong to the Basement Complex, and forming part of the Malawi Province of the Mozambique belt. Graphitic granulites and graphitic schists have been mapped throughout the licence area. This basement package was intruded by pegmatite bodies (dykes and sills).</li> </ul>
		<ul> <li>Metamorphosed mafic and ultramafic rocks have been observed in very few areas. Field evidence has supported that the basement rocks were subjected to upper amphibolite metamorphism as well as granulite facies conditions in several localities. In some areas the rocks are well exposed but for the most part they are covered by thick surficial deposits including residual soils, alluvium and colluvium which are believed to have formed due to prolonged weathering since mid-Tertiary.</li> <li>The basement rocks are complexly deformed but the pegmatite bodies are massive and undeformed.</li> </ul>



Criteria	Explanation	Commentary
Drill hole	• A summary of all information material	21/2
Information	to the understanding of the	• N/A
	exploration results including a	
	tabulation of the following	
	information for all Material drill holes:	
	• easting and northing of the drill	
	hole collar	
	<ul> <li>elevation or RL (Reduced Level –</li> </ul>	
	elevation above sea level in	
	metres) of the drill hole collar	
	<ul> <li>dip and azimuth of the hole</li> </ul>	
	down hole length and interception	
	depth	
	hole length.	
	• If the exclusion of this information is	
	justified on the basis that the	
	information is not Material and this	
	exclusion does not detract from the	
	understanding of the report, the	
	Competent Person should clearly	
Desta	explain why this is the case.	
Data	In reporting Exploration Results,	• The results shown are per sample
aggregation	weighting averaging techniques,	and are not weighed averages.
methoas	maximum and/or minimum grade	No sub off smaller have been smalled
	and cut off grades are usually	<ul> <li>No cut off grades have been applied to the results.</li> </ul>
	Material and should be stated	
	Where agaregate intercents	
	incorporate short lengths of high	
	arade results and longer lengths of	
	low arade results, the procedure used	
	for such gaaregation should be stated	
	and some typical examples of such	
	aggregations should be shown in	
	detail.	
	• The assumptions used for any	
	reporting of metal equivalent values	
	should be clearly stated.	
Relationship	These relationships are particularly	• N/A
between	important in the reporting of	
mineralisation	Exploration Results.	
widths and	• If the geometry of the mineralisation	
intercept	with respect to the drill hole angle is	
lengths	known, its nature should be reported.	
	If it is not known and only the down	
	noie lengths are reported, there	
	snould be a clear statement to this	
	ejject (eg. down nole length, true	
	width not known').	



Criteria	Explanation	Commentary
Diagrams	<ul> <li>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.</li> </ul>	<ul> <li>Appropriate maps are included in the body of the report</li> </ul>
Balanced reporting	<ul> <li>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</li> </ul>	<ul> <li>Reporting of results in this report is considered balanced.</li> <li>All results have been reported</li> </ul>
Other substantive exploration data	Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.	• N/A
Further work	<ul> <li>The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling).</li> <li>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</li> </ul>	• N/A